Texol Zero Air Generators

Our range of low maintenance Zero Air Generators that offer flexibility and outputs of up to 40L/min


Overview

Utilising catalytic combust technology the Apex Zero Air series provides clean hydrocarbon free air for the most demanding of applications. Once connected to a compressed air source the system has no moving parts and will provide no restriction to the air flow through the system with a minimised power requirement. All the models in our range are small enough that they will easily sit on a workbench.

The Zero Air series provides flexibility to match your system requirements. We can customise the purity, flow rate and delivery pressure to suit your specifications.

Features and benefits

- Flow Rates from 1 to 40 litres/min
- Output hydrocarbon content of <0.01 ppm
- Low Power requirement
- Rapid Start up
- Output Pressure up to 147 PSIg (10 Barg)
- Easy Installation
- Simple maintenance



How it works

Compressed air enters the generator via a filter [1] that removes contaminants and bulk moisture via an integrated auto drain. The air then enters a heated chamber containing the catalytic converter [2] Here any hydrocarbons are burnt off and converted into trace amounts of carbon dioxide and water. The now hot, hydrocarbon free air passes through a cooler [3] were it is returned to ambient temperature before finally passing through another filter [4] and exiting the system.



Technical specifications

| Model | ZA Small | ZA Medium | ZA large | ZA XL | |
|-------------------|--|----------------|------------|------------|--|
| Flow L/min | 1-6 | 8-18 | 20-28 | 30-40 | |
| Purity | Less than 0.01ppm total hydrocarbon content | | | | |
| Dew | | | | | |
| point (c PDP) | -10 | | | | |
| Pressure | From 1 Barg (14.7 PSIg) to 10 Barg (147 PSIg) | | | | |
| Start-up time | 3 minutes | | | | |
| Power | 230V at 50hz or 110V at 60hz Heater is only on for 1 minute in every 5 which results in low overall power use. | | | | |
| Depth (mm/ins) | 450 / 17.7 | 450 / 17.7 | 450 / 17.7 | 450 / 17.7 | |
| Height (mm/ins) | 303 / 11.9 | 303 / 11.9 | 303 / 11.9 | 303 / 11.9 | |
| Width (mm/ins) | 235 / 9.3 | 235 / 9.3 | 235 / 9.3 | 235 / 9.3 | |
| Weight (kg/lbs.) | 9 / 19.8 | 9 / 19.8 | 9 / 19.8 | 10 / 22 | |
| Ports | | Female ¼" BSPP | | | |

Contact details

Texol Gasgen Ltd Unit 36 Elderpark workspaces ElderPark Street Glasgow Scotland G51 3TR

Tel: +44 (0) 141 530 7417

Email: sales@texol.co.uk
Web: www.texol.co.uk

